Lenovo ThinkVision T24-40 Monitor

Seamless Visuals, Powerful Performance.



Lenovo



Helps save power at work

Match your screen to your workflow with the ThinkVision T24-40 Monitor's 48 Hz - 120 Hz variable refresh rate¹, optimized for seamless visuals while saving energy.



Combines clear images and comprehensive connectivity

Enjoy clear, distortion-free visuals with the ThinkVision T24-40 Monitor's 23.8-inch In-Plane Switching panel technology which delivers premium, vibrant colors from any viewing angle. Get more connected and compatible with a wide range of devices on T24-40's USB hubs, unlocking greater productivity for your workflows.



Boosts efficiency with Fleet Management

Manage and control your monitor assets with Lenovo Display Fleet Manager (LDFM). This innovative software solution empowers IT managers with robust tools for streamlined asset management, efficient firmware upgrades, and centralized settings control.

Lenovo ThinkVision

Lenovo ThinkVision T24-40 Monitor

Display

Panel Size 23.8-inch

Screen Dimensions 535.0 mm x 310.1 mm

Panel Type

4-sided Ultra Thin, In-Plane Switching

Active Area

Backlight WLED

Aspect Ratio 16.9

Resolution 1920 x 1080

Pixel Pitch 0.2745 mm x 0.2745 mm

Dot/Pixel Per Inch (DPI/PPI)

Viewing Angle (H x V @ CR 10:1) 178° / 178°

Response Time 4ms (Extreme Mode), 6ms (Normal Mode)

Refresh Rate 48 Hz - 120 Hz

Brightness 250 cd/m²

Contrast Ratio (Typical) 1500:1

Dynamic Contrast Ratio (Typical)

Color Gamut (Coverage Ratio) 99% sRGB, 99% BT.709

Color Support (Typical) 16.7 Million

Color Depth 8-bit

Anti-glare

Connectivity

Video Signal 1 x HDMI 1.4² 1x DP 12 1 x VGA

USB Upstream

1 x USB-B (USB 5Gbps / USB 3.2 Gen 1)3

USB Downstream

3 x USB-A (USB 5Gbps / USB 3.2 Gen 1)³ 1 x USB-C⁴ (USB 5Gbps / USB 3.2 Gen 1, Up to 15W PD (data only))³

Multimedia

Modular Camera/Soundbar Support Yes (Optional Support⁵)

Special Features

Software

and Display Manager) and LDFM (Lenovo Display Fleet Manager)⁶

Natural Low Blue Light Yes

Power

Power Consumption (Typ. / Max.)

Power Consumption Sleep/Off Mode

Power Consumption Switch-Off Mode

ENERGY STAR Power Consumption (Pon/E_{TEC})

Power Supply Internal

Voltage Required AC 100 to 240 V (50-60 Hz)

Mechanical

Tilt Angle (Front / Back) -5° / 23.5°

Swivel Angle (Left / Right) -45° / 45°

Lift (Max. Range) 155 mm

Pivot

-90° / 90°

VESA Mount Capability Yes (100 x 100 mm)

ThinkCentre M Series Tiny Support7

Kensington Lock Slot Yes (2.5 mm x 6 mm)

Cable Management

Bezel Color Raven Black

Bezel Width (Side)

Bezel Width (Top)

Bezel Width (Bottom)

Dimension

Size Packed (W x D x H, mm/inch) 28.90 x 4.41 x 16.61 inches

Size Unpacked w/ Stand (Highest Position) (W x D x H, mm/inch) 539.8 x 190.0 x 505.8 mm

21.25 x 7.48 x 19.91 inches

Size Unpacked w/ Stand (Lowest Position) (W x D x H, mm/inch) 539.8 x 190.0 x 350.8 mm 21 25 x 7 48 x 13 81 inches

Size Unpacked w/o Stand (Head Only) (W x D x H, mm/inch) 539.8 x 45.3 x 314.8 mm 21.25 x 1.78 x 12.39 inches

Weight Packed (kg / lbs.) 7.3 kg / 16.1lbs

Weight Unpacked (kg / lbs.) 5.1 kg / 11.2 lbs.

Weight (Monitor Head Only) (kg / lbs.) 3.0 kg / 6.6 lbs.

What's in the Box

Monitor with Stand Vac

Power Cable (Cable Length) 1 x Power Cable (1.8 m)

DP Cable (Cable Length)

1 x DP 1.2 Cable (1.8 m)

USB Cable (Cable Length) 1 x USB-A to USB-B Gen1 Cable (1.8m, 5Gbps)

Quick Setup Guide Vac

Certification

ENERGY STAR Certification Yes

TCO 10.0

TCO Edge

EPEAT Gold

Windows Certification Windows 10, Windows 11

EU Energy Level Certification Yes (Level-C)

China Energy Efficiency Standard Tier 1

TÜV Rheinland Eye Comfort 5 Stars

TÜV Rheinland Low Blue Light Yes

TÜV Rheinland Flicker Free Yes

TÜV Low Blue Light (Hardware Solution) Yes

Eyesafe Display Certification Yes (Eyesafe 2.0)

















VRR as specified in HDMI 2.1, DRR for Microsoft Windows. | ² Supports 1920 x 1080 @ 120 Hz as specified in HDMI 1.4. | ³ The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s; USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1) 5 Gbit/s; USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2) 10 Gbit/s; USB4* 20Gbps / USB 3.2 Gen 2 x22 (SuperSpeed USB 20Gbps) 20 Gbit/s; USB4* 40Gbps (USB 40Gbps) 40 Gbit/s; Thunderbolt* 3/4: 40 Gbit/s. | ⁴ USB Type-C are registered trademarks of USB Implementers Forum. | ⁵ Compatible with ThinkVision Volley Stack McG0 Monitor Webcam and MS30 Monitor Soundbar, | ⁶ Formerly Lenovo Display Control Center. Supports Windows 10 & 11, Mac OS (functions vary across systems). | ⁷ Sold separately. Need to ensemble Tiny Clamp together with the VESA mount to mount the Tiny & Tiny VESA Mount II (PN: 4XF0N03161).

© 2025 Lenovo. All rights reserved. These products are available while supplies last. Prices shown are subject to change without notice. For any questions concerning price, please contact your Lenovo Account Executive. Lenovo is not responsible for photographic or typographic errors. Warranty: For a copy of applicable warranties, write to: Warranty Information, 500 Park Offices Drive, RTP, NC 27709, U.S.A, Attn: Dept. ZPYA/B600. Lenovo makes no representation or warranty regarding third-party products or services. Trademarks: Lenovo, the Lenovo logo, Rescue and Recovery, ThinkPad, ThinkStation, ThinkVantage, ThinkVision, and ThinkColour are trademarks or registered trademarks of Lenovo. Microsoft, Windows, and Vista are registered trademarks of Microsoft Corporation. Intel, the Intel logo, Intel Inside, Intel Core, and Core Inside are trademarks of Intel Corporation in the U.S. and/or other countries. Other company, product, and service names may be trademarks or service marks of others. Specifications may vary depending upon region